

# Sizing, installation, dimensions and weights GOLD PX & GOLD CX

The charts and tables in this documentation are intended for use as a general survey.

Exact sizing can be carried out in the AHU Design air handling unit selection program.

## Contents

GOLD PX

Size 004..... 74

Size 005..... 78

Size 007..... 82

Size 008..... 86

Size 011..... 90

Size 012..... 93

Size 014/020 ..... 96

Size 025/030 ..... 100

Size 035/040/040+ ..... 104

Size 050+/060+ ..... 108

GOLD CX

Size 035/040 ..... 111

Size 050/060 ..... 114

Size 070/080 ..... 117

Size 100..... 120

Size 120..... 122


Electrical data

GOLD PX size 014-040..... 124

GOLD CX size 035-120..... 125

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 004



- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
004	288	0.08	1620	0.45

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 004, common casing

### Delivery and transport within the site

The GOLD PX 004 is produced in one single variant. All of its components are arranged at their given physical locations inside the air handling unit.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


The air handling unit is supplied on a wooden pallet.

The set of support legs, for mounting the base beams, is available as an accessory.


### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.

**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).




Right-hand version



Left-hand version

Outdoor air Supply air Extract air Exhaust air



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	F	G	H	J	L	Ø	Weight, kg
004	822	825	240	345	230	460	920	579	2333	315	349-387

### Clear Space for Inspection

A clear space of 900 mm must be provided in front of the unit and at least 200 mm must be provided above the junction hood.

### Power connection

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 10 A or  
3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

Motor shaft power: 1.15 kW (0.41 kW)\*  
motor control system, 1 x 230 V, 50 Hz

\*The motor control system limits the power of the take-off to the value specified.

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 004, split version

### Delivery and transport within the site

The GOLD PX 004 can be supplied as one single unit, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit/ Delivery Configuration RX/PX/CX, sizes 004-080.



The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.

The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.

### Duct connection options

- A:** Specify right-hand or left-hand version when ordering.
- B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).




If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	F	G	H	J	K	L	Ø	Weight, kg
004	617	825	240	1300	230	460	920	579	345	2534	315	438-490

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 88-112 kg, D = 262-266 kg.

### Power connection

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 10 A or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

Motor shaft power 1.15 kW (0.41 kW)\*, Motor control system: 1 x 230 V, 50 Hz

\*The motor control system limits the output power to the value specified.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

# Sizing, installation, dimensions and weights

## GOLD PX Top, counterflow heat exchanger, size 004

### Delivery and transport within the site

GOLD PX Top 004 can be supplied as one single unit or in an optional division of sections. Extra air handling unit sections cannot be ordered due to the deviating height measurement. Filter/fan sections for height adapted PX (side fed) and PX Top can be combined, see the section: Description of the Air Handling Unit.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.


The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


### Duct connection options

**A:** All the duct connections are arranged from the top of the air handling unit (the unit must not be installed outdoors).

**B:** Specify right-hand or left-hand version when ordering.






Right-hand version



Left-hand version


Outdoor air    Supply air    Extract air    Exhaust air



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

Size	A	B	D	E	F	H	I	J	L	Ø	Weight, kg
004	617	825	1300	334	798	1085	238	579	2534	315	480-484

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 109 kg, D = 262-266 kg.

### Electrical connection

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 10 A or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

Motor shaft power 1.15 kW (0.41 kW)\*, motor control system: 1 x 230 V, 50 Hz


\*The motor control system limits the output power to the value specified.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 005



Motor shaft power: 1.15 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. air flows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
005	288	0.08	2340	0.65

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 005, common casing

### Delivery and transport within the site

The GOLD PX 005 is produced in one single variant, in which all the components are arranged at their given physical locations inside the air handling unit.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


The air handling unit is supplied on a wooden pallet.

The set of support legs, for mounting the base beams, is available as an accessory.


### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.





**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).




Right-hand version



Left-hand version





 Outdoor air Supply air Extract air Exhaust air



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	F	G	H	J	L	Ø	Weight, kg
005	822	825	240	345	230	460	920	579	2333	315	349-387

### Clear Space for Inspection

A clear space of 900 mm must be provided in front of the unit and at least 200 mm must be provided above the junction hood.

### Power connection

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 10 A (capacity variant 1) alt. 16 A (capacity variant 2) or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

Motor shaft power: 1.15 kW (0.8 kW\* or 1.15 kW), motor control system: 1 x 230 V, 50 Hz

\*The motor control system limits the output power to the value specified.

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 005, split version

#### Delivery and transport within the site

The GOLD PX 005 can be supplied as one single unit, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit/ Delivery Configuration RX/PX/CX, sizes 004-080.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.



The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.

#### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.

**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).




If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	F	G	H	J	K	L	Ø	Weight, kg
005	617	825	240	1300	230	460	920	579	345	2534	315	438-490

#### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 88-112 kg, D = 262-266 kg.

#### Power connection

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 10 A (capacity variant 1) or 16 A (capacity variant 2) or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

#### Rated data per fan

Motor shaft power: 1.15 kW (0.8 kW\* or 1.15 kW), motor control system: 1 x 230 V, 50 Hz

\*The motor control system limits the output power to the value specified.

#### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.



# Sizing, installation, dimensions and weights

## GOLD PX Top, counterflow heat exchanger, size 005

### Delivery and transport within the site

GOLD PX Top 005 can be supplied as one single unit or in an optional division of sections. Extra air handling unit sections cannot be ordered due to the deviating height measurement. Filter/fan sections for height adapted PX (side fed) and PX Top can be combined, see the section: Description of the Air Handling Unit.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.


The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


### Duct connection options

**A:** All the duct connections are arranged from the top of the air handling unit (the unit must not be installed outdoors).

**B:** Specify right-hand or left-hand version when ordering.





Right-hand version




Left-hand version

Outdoor air    Supply air    Extract air    Exhaust air




Power connection



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

Size	A	B	D	E	F	H	I	J	L	Ø	Weight, kg
005	617	825	1300	334	798	1085	238	579	2534	315	480-492

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 109-113 kg, D = 262-266 kg.

### Electrical connection

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 10 A (capacity variant 1) or 16 A (capacity variant 2) or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

Motor shaft power: 1.15 kW (0.8 kW\* or 1.15 kW), motor control system: 1 x 230 V, 50 Hz


\*The motor control system limits the output power to the value specified.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 007



- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. air flows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
007	288	0.08	2700	0.75

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 007, common casing

### Delivery and transport within the site

The GOLD PX 007 is produced in one single variant. All of its components are arranged at their given physical locations inside the air handling unit.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


The air handling unit is supplied on a wooden pallet.

The set of support legs, for mounting the base beams, is available as an accessory.


### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.

**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).




Right-hand version



Left-hand version

Outdoor air  
 Supply air  
 Extract air  
 Exhaust air



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	F	G	H	J	L	Ø	Weight, kg
007	911,5	995	277,5	440	271	543	1085	749	2503	400	435-492

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

### Power connection

#### Capacity variant 1:

1-phase, 3-conductor, 230 V -10/+15%, 50 Hz, 10 A or  
3-phase, 5-conductor, 400 V -10/+15%, 50 Hz, 10 A

#### Capacity variant 2:

1-phase, 3-conductor, 230 V -10/+15%, 50 Hz, 16 A or  
3-phase, 5-conductor, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

Motor shaft power: 1.15 kW (0.8 kW\* or 1.15 kW),  
motor control system: 1 x 230 V, 50 Hz

\*The motor control system limits the output power to the value specified.

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 007, split version

#### Delivery and transport within the site

The GOLD PX 007 can be supplied as one single unit, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit/ Delivery Configuration RX/PX/CX, sizes 004-080.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.


The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


#### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.

**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).




Right-hand version



Left-hand version

Outdoor air    Supply air    Extract air    Exhaust air




If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	F	G	H	J	K	L	Ø	Weight, kg
007	647	995	277.5	1517	271	543	1085	749	440	2811	400	547-623

#### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 103-138 kg, D = 341-347 kg.

#### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

#### Power connection

##### Capacity variant 1:

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 10 A or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

##### Capacity variant 2:

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 16 A or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

#### Rated data per fan

Motor shaft power: 1.15 kW (0.8 kW\* or 1.15 kW), motor control system: 1 x 230 V, 50 Hz

\*The motor control system limits the output power to the value specified.

# Sizing, installation, dimensions and weights

## GOLD PX Top, counterflow heat exchanger, size 007

### Delivery and transport within the site

GOLD PX Top 007 can be supplied as one single unit or in an optional division of sections. Extra air handling unit sections cannot be ordered due to the deviating height measurement. Filter/fan sections for height adapted PX (side fed) and PX Top can be combined, see the section: Description of the Air Handling Unit.

The unit sections are jointed together/split by means of bolts.

The electrical and control cables between the unit sections have quick-fit connectors.


The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


### Duct connection options

**A:** All the duct connections are arranged from the top of the air handling unit (the unit must not be installed outdoors).

**B:** Specify right-hand or left-hand version when ordering.




Right-hand version



Left-hand version

Outdoor air    Supply air    Extract air    Exhaust air




Electrical connection

If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

Size	A	B	D	E	F	H	I	J	K	L	Ø	Weight, kg
007	647	995	1517	350	878	1295	288	749	278	2811	400	599-613

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 129-133 kg, D = 341-347 kg.

### Electrical connection

**Capacity variant 1:**

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 10 A or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

**Capacity variant 2:**

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 16 A or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

Motor shaft power: 1.15 kW (0.8 kW\* or 1.15 kW), motor control system: 1 x 230 V, 50 Hz


\*The motor control system limits the output power to the value specified.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 008



- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero. However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

### Min. and max. air flows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
008	720	0.20	3600	1.00

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 008, common casing

### Delivery and transport within the site

The GOLD PX 008 is produced in one single variant. All of its components are arranged at their given physical locations inside the air handling unit.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


The air handling unit is supplied on a wooden pallet.

The set of support legs, for mounting the base beams, is available as an accessory.


### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.



**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).



Right-hand version



Left-hand version



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	F	G	H	J	L	Ø	Weight, kg
008	911,5	995	277,5	440	271	543	1085	749	2503	400	449-506

### Clear Space for Inspection

A clear space of 900 mm must be provided in front of the unit and at least 200 mm must be provided above the junction hood.

### Power connection

#### Capacity variant 1:

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 16 A or  
3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

#### Capacity variant 2:

3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

#### Capacity variant 1:

Motor shaft power: 1.15 kW,  
motor control system: 1 x 230 V, 50 Hz

#### Capacity variant 2:

Motor shaft power: 1.6 kW,  
motor control system: 3 x 400 V, 50 Hz

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 008, split version

### Delivery and transport within the site

The GOLD PX 008 can be supplied as one single unit, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit/ Delivery Configuration RX/PX/CX, sizes 004-080.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.


The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.

**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).




Right-hand version



Left-hand version

Outdoor air    Supply air    Extract air    Exhaust air




If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	F	G	H	J	K	L	Ø	Weight, kg
008	647	995	277.5	1517	271	543	1085	749	440	2811	400	561-631

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 110-142 kg, D = 341-347 kg.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

### Power connection

#### Capacity variant 1:

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 16 A or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

#### Capacity variant 2:

3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

#### Capacity variant 1:

Motor shaft power: 1.15 kW, motor control system: 1 x 230 V, 50 Hz

#### Capacity variant 2:


Motor shaft power: 1.6 kW, motor control system: 3 x 400 V, 50 Hz





## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 011



Motor shaft power: 1.6 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. air flows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
011	720	0.20	3960	1.10

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights



## GOLD PX, counterflow heat exchanger, size 011

### Delivery and transport within the site

The GOLD PX 011 can be supplied as one single unit, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit. Filter/fan sections for PX and PX Top can be combined, see the section: Description of the Air Handling Unit. The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors. The air handling unit/unit sections is/are delivered on wooden beams. The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.

### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.  
**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).




If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	E	F	G	H	J	K	L	Ø	Weight, kg
011	647	1199	324	1631	471	324	647	1295	953	551	2925	500	714-804

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 135-175 kg,  
D = 444-454 kg.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

### Power connection

#### Capacity variant 1:

1-phase, 3-conductor, 230 V -10/+15%, 50 Hz, 16 A or  
3-phase, 5-conductor, 400 V -10/+15%, 50 Hz, 10 A

#### Capacity variant 2:

3-phase, 5-conductor, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

#### Capacity variant 1:

Motor shaft power: 1.15 kW,  
motor control system: 1 x 230 V, 50 Hz

#### Capacity variant 2:

Motor shaft power: 1.6 kW,  
motor control system: 3 x 400 V, 50 Hz

# Sizing, installation, dimensions and weights


## GOLD PX Top, counterflow heat exchanger, size 011

### Delivery and transport within the site


The GOLD Top PX 011 can be supplied as two units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit. Filter/fan sections for PX and PX Top can be combined, see the section: Description of the Air Handling Unit. The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors. The air handling unit/unit sections is/are delivered on wooden beams. The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.

### Duct connection options

**A:** All the duct connections are arranged from the top of the air handling unit (the unit must not be installed outdoors).  
**B:** Specify right-hand or left-hand version when ordering.





Right-hand version




Left-hand version

Outdoor air    Supply air    Extract air    Exhaust air




Electrical connection



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

Size	A	B	D	E	F	H	I	J	L	Ø	Weight, kg
011	827	1199	1631	332	500	1295	332	953	3285	500	814-826

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 185-186 kg, D = 444-454 kg.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

### Electrical connection

#### Capacity variant 1:

1-phase, 3-wire, 230 V -10/+15%, 50 Hz, 16 A or 3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

#### Capacity variant 2:

3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

#### Capacity variant 1:


Motor shaft power: 1.15 kW, motor control system: 1 x 230 V, 50 Hz

#### Capacity variant 2:

Motor shaft power: 1.6 kW, motor control system: 3 x 400 V, 50 Hz

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 012



Motor shaft power: 2.4 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

### Min. and max. air flows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
012	720	0.20	5040	1.40

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 012


### Delivery and transport within the site

The GOLD PX 012 can be supplied as one single unit, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit. Filter/fan sections for PX and PX Top can be combined, see the section: Description of the Air Handling Unit. The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors. The air handling unit/unit sections is/are delivered on wooden beams. The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.

**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).



Outdoor air   
 Supply air   
 Extract air   
 Exhaust air




If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

Size	A	B	C	D	E	F	G	H	J	K	L	Ø	Weight, kg
012	647	1199	324	1631	471	324	647	1295	953	551	2925	500	736-832

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 146-189 kg,  
D = 444-454 kg.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

### Power connection

3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan

Motor shaft power: 2.4 kW (1.6 kW\* or 2.4 kW),  
motor control system: 3 x 400 V, 50 Hz

\*The motor control system limits the output power to the value specified.

# Sizing, installation, dimensions and weights

## GOLD PX Top, counterflow heat exchanger, size 012

### Delivery and transport within the site

The GOLD Top PX 012 can be supplied as two units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit. Filter/fan sections for PX and PX Top can be combined, see the section: Description of the Air Handling Unit.

The unit sections are jointed together/split by means of bolts.

The electrical and control cables between the unit sections have quick-fit connectors.


The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


### Duct connection options

**A:** All the duct connections are arranged from the top of the air handling unit (the unit must not be installed outdoors).

**B:** Specify right-hand or left-hand version when ordering.





Right-hand version




Left-hand version

Outdoor air    Supply air    Extract air    Exhaust air




Electrical connection



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

Size	A	B	D	E	F	H	I	J	L	Ø	Weight, kg
012	827	1199	1631	332	500	1295	332	953	3285	500	836-854

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 196-200 kg, D = 444-454 kg.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

### Electrical connection

3-phase, 5-wire, 400 V -10/+15%, 50 Hz, 10 A

### Rated data per fan


Motor shaft power: 2.4 kW (1.6 kW\* or 2.4 kW), motor control system: 3 x 400 V, 50 Hz

\*The motor control system limits the output power to the value specified.

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 014/020

Size 014 (Extract air fan size 020 can be selected, see the next page)



Motor shaft power: 2.4 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
014	720	0.20	5940	1.65


Exact sizing can be carried out in the AHU Design air handling unit selection program



## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 014/020

Size 020 (Extract air fan size 014 can be selected, see the previous page)



Motor shaft power: 3.4 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
020	1080	0.30	7560	2.1

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights


## GOLD PX, counterflow heat exchanger, size 014/020

### Delivery and transport within the site


The GOLD PX 014/020 can be supplied as two units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit. Filter/fan sections for PX and PX Top can be combined, see the section: Description of the Air Handling Unit. The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors. The air handling unit/unit sections is/are delivered on wooden beams. The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.

### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.  
**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).





Right-hand version



Left-hand version

Outdoor air    Supply air    Extract air    Exhaust air




\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

Size	A	B	D	E	F	G	H	I	J	K	L	M	N	Weight, kg
014/020	757,5	1400	1836	528	400	1000	1551	375	1154	200	3351	205	188	929-1089

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 190-264 kg, D = 549-561 kg.

### Rated data per fan

Size 014: Motor shaft power: 2.4 kW (1.6 kW\* or 2.4 kW), motor control system: 3 x 400 V, 50 Hz  
 \*The motor control system limits the output power to the value specified.  
 Size 020: Motor shaft power: 2.4 kW alt. 3.4 kW, motor control system: 3 x 400 V, 50 Hz

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.

### Electrical connection

See table Electrical data at the end of this section.

# Sizing, installation, dimensions and weights

## GOLD PX Top, counterflow heat exchanger, size 014/020

### Delivery and transport within the site

The GOLD Top PX 014/020 can be supplied as two units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit. Filter/fan sections for PX and PX Top can be combined, see the section: Description of the Air Handling Unit.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.


The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


### Duct connection options

**A:** All the duct connections are arranged from the top of the air handling unit (the unit must not be installed outdoors).

**B:** Specify right-hand or left-hand version when ordering.




Right-hand version




Left-hand version

Outdoor air    
 Supply air    
 Extract air    
 Exhaust air




If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.



Size	A	B	D	E	F	G	H	I	J	K	L	M	N	O	P	Weight, kg
014/020	1039	1400	1836	120	400	1000	1551	106	1154	528	3914	300	1200	200	100	1083-1175

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 267-307 kg, D = 549-561 kg.

### Rated data per fan

Size 014: Motor shaft power: 2.4 kW (1.6 kW\* or 2.4 kW), motor control system: 3 x 400 V, 50 Hz  
*\*The motor control system limits the output power to the value specified.*

Size 020: Motor shaft power: 2.4 kW alt. 3.4 kW, motor control system: 3 x 400 V, 50 Hz

### Clear space for inspection

A clear space of 1000 mm should be provided in front of the unit and at least 200 mm should be provided above the junction hood.


### Electrical connection

See table Electrical data at the end of this section.

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 025/030

Size 025 (Extract air fan size 030 can be selected, see the next page)



Motor shaft power: 3.4 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.


Size	Min. airflow (on airflow regulation)		Max. airflow	
	m <sup>3</sup> /h	m <sup>3</sup> /s	m <sup>3</sup> /h	m <sup>3</sup> /s
025	1080	0.30	9000	2.50

Exact sizing can be carried out in the AHU Design air handling unit selection program

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 025/030

Size 030 (Extract air fan size 025 can be selected, see the previous page)



Motor shaft power: 5.0 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
030	1800	0.50	11520	3.20

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 025/030

### Delivery and transport within the site

The GOLD PX 025/030 can be supplied as two units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit. Filter/fan sections for PX and PX Top can be combined, see the section: Description of the Air Handling Unit.



The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.

The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.

### Duct connection options

- A:** Specify right-hand or left-hand version when ordering.
- B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).




\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.

Size	A	B	D	E	F	G	H	I	J	K	L	M	N	Weight, kg
025/030	847,5	1600	2130	675	500	1200	1811	405	1354	200	3825	200	203	1235-1451

### Division into sections for transport



The unit can be divided into three sections at the building site.  
**Dimensions:** See A and D in the table above.  
**Weight:** A = 249-345 kg, D = 737-761 kg.

### Clear space for inspection

A clear space of 900 mm should be provided in front of the unit.

### Rated data per fan

- Size 025: Motor shaft power 2.4 kW alt. 3.4 kW, motor control system: 3 x 400 V, 50 Hz
- Size 030: Motor shaft power: 4.0 kW alt. 5.0 kW, motor control system: 3 x 400 V, 50 Hz

### Electrical connection

See table Electrical data at the end of this section.

# Sizing, installation, dimensions and weights

## GOLD PX Top, counterflow heat exchanger, size 025/030

### Delivery and transport within the site

The GOLD Top PX 025/030 can be supplied as two units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit. Filter/fan sections for PX and PX Top can be combined, see the section: Description of the Air Handling Unit.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.


The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


### Duct connection options

**A:** All the duct connections are arranged from the top of the air handling unit (the unit must not be installed outdoors).

**B:** Specify right-hand or left-hand version when ordering.




Right-hand version




Left-hand version

Outdoor air    
 Supply air    
 Extract air    
 Exhaust air




If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.



Size	A	B	D	E	F	G	H	I	J	K	L	M	N	O	P	Weight, kg
025/030	1039	1600	2130	120	400	1200	1811	106	1354	675	4208	300	1400	200	100	1375-1513

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 319-376 kg, D = 737-761 kg.

### Clear space for inspection

A clear space of 1,000 mm should be provided in front of the unit.

### Rated data per fan

Size 025: Motor shaft power 2.4 kW alt. 3.4 kW, motor control system: 3 x 400 V, 50 Hz

Size 030: Motor shaft power: 4.0 kW alt. 5.0 kW, motor control system: 3 x 400 V, 50 Hz


### Electrical connection

See table Electrical data at the end of this section.

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 035/040

Size 035 (Extract air fan size 040 can be selected, see the next page)



Motor shaft power: 5.0 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
035	1800	0.50	14040	3.90


Exact sizing can be carried out in the AHU Design air handling unit selection program



## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 035/040

Size 040 (Extract air fan size 035 can be selected, see the previous page)



Motor shaft power: 10 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
040	2700	0.75	18000	5.00

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 035/040

### Delivery and transport within the site

The GOLD PX 035/040 can be supplied as three units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit/ Delivery Configuration RX/PX/CX, sizes 011-080.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.


The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.


### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.



**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).



Right-hand version




Left-hand version




\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected. The AHU can also be supplied with full face end connection panel (accessory).

If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose.



Size	A	B	D	E	F	G	H	I	J	K	L	N	Weight, kg
035/040	1038.5	1990	2400	806	600	1400	2159	479	1744	295	4477	240	1792-2082

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 377-504 kg, D = 1038-1074 kg.

### Clear space for inspection

A clear space of 1,100 mm should be provided in front of the unit.

### Rated data per fan

Size 035: Motor shaft power: 4.0 kW alt. 5.0 kW, motor control system, 3 x 400 V, 50 Hz  
Size 040: Motor shaft power: 6.5 kW alt. 10 kW, motor control system, 3 x 400 V, 50 Hz

### Electrical connection

See table Electrical data at the end of this section.

# Sizing, installation, dimensions and weights

## GOLD PX, counterflow heat exchanger, size 040+

### Delivery and transport within the site

GOLD PX 040+ is always supplied as four units, two fan/filter sections and the heat exchanger section in two parts.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.



The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.

### Duct connection options


**A:** Specify right-hand or left-hand version when ordering.

**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units).



Size	A	B1	B2	D	E	F	G	H	I	K	L	N	P1/P2	Weight, kg
040+	1038.5	2446	1990	2430	821	600	1400	2159	479	295	4507	240	1223	2180-2462

### Division into sections for transport



Dimensions and weights of the four delivery units.

**Dimensions:** See A, D and P1/P2 in the table above.

**Weight:** A = 377-504 kg,  
D/P1 = 733-747 kg,  
D/P2 = 693-707 kg.

### Clear space for inspection

A clear space of 1100 mm should be provided in front of the unit.

### Rated data per fan

Size 040: Motor shaft power: 6.5 kW or 10 kW,  
motor control system: 3 x 400 V, 50 Hz


### Electrical connection

See table Electrical data at the end of this section.

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 050/060

Size 050 (Extract air fan size 060 can be selected, see the next page)



Motor shaft power 10 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero. However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.


Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
050	2,700	0.75	18,000	5.00

Exact sizing can be carried out in the AHU Design air handling unit selection program

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 050/060

Size 060 (Extract air fan size 050 can be selected, see the previous page)



- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero. However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m <sup>3</sup> /h	m <sup>3</sup> /s	m <sup>3</sup> /h	m <sup>3</sup> /s
060	3,600	1.00	23,400	6.50

Exact sizing can be carried out in the AHU Design air handling unit selection program

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 050+/060+

#### Delivery and transport within the site

GOLD PX 050+/060+ is always supplied as four units, two fan/filter sections and the heat exchanger section in two parts.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.



The air handling unit/unit sections is/are delivered on wooden beams.

The electrical cabinet and the drain pipe on the front of the air handling unit can be removed, if required, for transporting the unit within the building site.

#### Duct connection options


**A:** Specify right-hand or left-hand version when ordering.

**B:** Specify whether the unit shall have an air intake from above for outdoor air and/or extract air when placing orders (does not apply to outdoor units). N.B.! Duct connection size: 2000 x 600 mm.



Size	A	B1	B2	D	E	F	G	H	I	K	L	M	N	O	P1/P2	Weight, kg
050+/060+	1038.5	2446	2318	2430	821	800	1600	2288	344	359	4507	600	172	2000	1223	2290-2690

#### Division into sections for transport



Dimensions and weights of the four delivery units.

**Dimensions:** See A, D and P1/P2 in the table above.

**Weight:** A = 444-630 kg,  
D/P1 = 721-695 kg,  
D/P2 = 681-735 kg.

#### Clear space for inspection

A clear space of 1100 mm should be provided in front of the unit.

#### Rated data per fan

Size 050: Motor shaft power: 6.5 kW or 10 kW,  
motor control system: 3 x 400 V, 50 Hz

Size 060: Motor shaft power: 2 x 4.0 kW or 2 x 6.5 kW,  
motor control system: 3 x 400 V, 50 Hz


#### Electrical connection

See table Electrical data at the end of this section.

## Sizing, installation, dimensions and weights

### GOLD CX, coil heat exchangers, size 035/040

Size 035 (Extract air fan size 040 can be selected, see the next page)



- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.


Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
035	1800	0.50	14040	3.90

Exact sizing can be carried out in the AHU Design air handling unit selection program

## Sizing, installation, dimensions and weights

### GOLD CX, coil heat exchangers, size 035/040

Size 040 (Extract air fan size 035 can be selected, see the previous page)



Motor shaft power: 10 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
040	2700	0.75	18000	5.00

Exact sizing can be carried out in the AHU Design air handling unit selection program



# Sizing, installation, dimensions and weights

## GOLD CX, coil heat exchangers, size 035/040

### Delivery and transport within the site

The GOLD CX 035/040 is supplied in three units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit/Delivery Configuration RX/PX/CX, sizes 011-080.

The unit sections are jointed together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.

The air handling unit/unit sections is/are delivered on wooden beams.

The coil heat exchanger system is filled with liquid from the factory.




### Duct connection options

**A:** Specify right-hand or left-hand version when ordering. If the air handling unit is supplied with all the end connection panels, the version can be changed at the building site using the hand-held terminal.

**B:** The arrangement of the functional sections can be vertically reversed. To be specified when placing an order, see the illustration to the right.

**C:** Specify upper fan outlet for upward air discharge when placing orders (not for outdoor units).

**D:** Specify whether the unit shall have an air intake from above for outdoor air or extract air when placing orders (Does not apply to units installed outdoors).



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Support feet (accessories) can be used for this purpose. Applies to right-hand version with the supply air fan to the upper right and to left-hand version with the supply air fan to the upper left.


\* The air handling unit is supplied without end connection panel if a duct accessory housed in an insulated casing will be connected.

The AHU can also be supplied with full face end connection panel (accessory).

\*\* Width of centre section's casing =  $B + 200$  mm.

Size	A	B	C	D	E	F	G	H	I	J	K	L	Weight, kg
035/040	1038.5	1990	1744	900	245	600	1400	2159	479	240	295	2977	1934-2188

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 377-504 kg, D = 1,180 kg.

### Clear space for inspection

A clear space of 1,100 mm should be provided in front of the unit.

### Rated data per fan

Size 035: Motor shaft power: 4.0 kW alt. 5.0 kW, motor control system, 3 x 400 V, 50 Hz

Size 040: Motor shaft power: 6.5 kW alt. 10 kW, motor control system: 3 x 400 V, 50 Hz


### Electrical connection

See table Electrical data at the end of this section.

## Sizing, installation, dimensions and weights

### GOLD CX, coil heat exchangers, size 050/060

Size 050 (Extract air fan size 060 can be selected, see the next page)



Motor shaft power: 10 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.


Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
050	2700	0.75	18000	5.00

Exact sizing can be carried out in the AHU Design air handling unit selection program

## Sizing, installation, dimensions and weights

### GOLD CX, coil heat exchanger, size 050/060

Size 060 (Extract air fan size 050 can be selected, see the previous page)



Motor shaft power: 2 x 6.5 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
060	3600	1.00	23400	6.50

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD CX, coil heat exchangers, size 050/060

### Delivery and transport within the site

The GOLD CX 050/060 is supplied in three units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit/Delivery Configuration RX/PX/CX, sizes 011-080.

The unit sections are joined together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors

The air handling unit/unit sections is/are delivered on wooden beams.

The coil heat exchanger system is filled with liquid from the factory.


### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.

**B:** The arrangement of the functional sections can be vertically reversed. To be specified when placing an order, see the illustration to the right.



**C:** Specify upper fan outlet for upward air discharge when placing orders (not for outdoor units).

**D:** Specify whether the unit shall have an air intake from above for outdoor air or extract air when placing orders (Does not apply to units installed outdoors). N.B.! Duct connection size: 2,000 x 600 mm.



\* If the duct accessory is housed in an insulated casing, the AHU is supplied without the end connection panel. The AHU can also be supplied with full face end connection panel (accessory).


\*\* Width of centre section's casing =  $B + 200$  mm.



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Adjustable support feet (accessories) can be appropriately fitted to the base beams for this purpose. Applies to right-hand version with the supply air fan to the upper right and to left-hand version with the supply air fan to the upper left.

Size	A	B	D	E	F	G	H	I	J	K	L	M	N	O	Weight, kg
050/060	1038,5	2318	900	145	800	1600	2288	344	172	359	2977	600	159	2000	2346-2718

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 444-630 kg, D = 1458 kg.

### Clear space for inspection

A clear space of 1,100 mm should be provided in front of the unit.

### Rated data per fan

Size 050: Motor shaft power: 6.5 kW alt. 10 kW, motor control system: 3 x 400 V, 50 Hz

Size 060: Motor shaft power: 2 x 4.0 kW alt. 2 x 6.5 kW, motor control system: 3 x 400 V, 50 Hz


### Electrical connection

See table Electrical data at the end of this section.

## Sizing, installation, dimensions and weights

### GOLD CX, coil heat exchangers, size 070/080

Size 070 (Extract air fan size 080 can be selected, see the next page)



Motor shaft power: 2 x 6.5 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.


Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
070	3600	1.00	27000	7.50

Exact sizing can be carried out in the AHU Design air handling unit selection program

## Sizing, installation, dimensions and weights

### GOLD CX, coil heat exchangers, size 070/080

Size 080 (Extract air fan size 070 can be selected, see the previous page)



Motor shaft power: 2 x 10 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero.
- However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

#### Min. and max. airflows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
080	5400	1.50	34200	9.50

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD CX, coil heat exchangers, size 070/080

### Delivery and transport within the site

The GOLD CX 070/080 is supplied in three units, or in a number of different combinations of unit sections from the factory, see the section: Description of the Air Handling Unit/Delivery Configuration RX/PX/CX, sizes 011-080.

The unit sections are joined together/split by means of bolts. The electrical and control cables between the unit sections have quick-fit connectors.

The coil heat exchanger system is filled with liquid from the factory.


### Duct connection options

**A:** Specify right-hand or left-hand version when ordering.

**B:** The arrangement of the functional sections can be vertically reversed. To be specified when placing an order, see the illustration to the right.



**C:** Specify upper fan outlet for upward air discharge when placing orders (not for outdoor units).

**D:** Specify whether the unit shall have an air intake from above for outdoor air or extract air when placing orders (Does not apply to units installed outdoors). N.B.! Duct connection size: 2,400 x 750 mm.



\* If the duct accessory is housed in an insulated casing, the AHU is supplied without the end connection panel. The AHU can also be supplied with full face end connection panel (accessory).


\*\* Width of centre section's casing =  $B + 200$  mm.



If a water trap (accessory) is fitted, the air handling unit must be raised at least 50 mm to provide space for the water trap. Adjustable support feet (accessories) can be appropriately fitted to the base beams for this purpose. Applies to right-hand version with the supply air fan to the upper right and to left-hand version with the supply air fan to the upper left.

Size	A	B	D	E	F	G	H	I	J	K	L	M	N	O	Weight, kg
070/080	1273,5	2637	900	162	1000	1800	2640	320	160	418,5	3447	750	118,5	2400	3454-3794

### Division into sections for transport



The unit can be divided into three sections at the building site.

**Dimensions:** See A and D in the table above.

**Weight:** A = 786-956 kg, D = 1882 kg.

### Clear space for inspection

A clear space of 1,100 mm should be provided in front of the unit.

### Rated data per fan

Size 070: Motor shaft power: 2 x 4.0 kW alt. 2 x 6.5 kW, motor control system: 3 x 400 V, 50 Hz


Size 080: Motor shaft power: 2 x 6.5 kW alt. 2 x 10 kW, motor control system: 3 x 400 V, 50 Hz

### Electrical connection

See table Electrical data at the end of this section.

# Sizing, installation, dimensions and weights

## GOLD CX, coil heat exchangers, size 100



Motor shaft power: 2 x 10 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero. However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

### Min. and max. air flows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
100	5400	1.50	39600	11.0

Exact sizing can be carried out in the AHU Design air handling unit selection program



# Sizing, installation, dimensions and weights

## GOLD CX, coil heat exchangers, size 100

### Delivery and transport within the site

The GOLD CX 100 is supplied as six separate sections: Two fan sections, two filter sections and two coil heat exchanger sections. The six sections must be fitted together at the building site. The pipework package including the control box can be ordered as accessories and are supplied in unassembled condition for floor or wall mounting (see TBXZ pipework package under Accessories).



The three sections are to be jointed together by bolts and the electrical and control cables are simple to connect.

### Duct connection options


**A:** Specify right-hand or left-hand version when ordering.

**B:** The arrangement of the functional sections can vary. Specify this by selecting fan arrangement 1, 2, 4 or 5 when placing orders. For fan arrangement 4 and 5, you should also specify: supply air in upper or lower level.

**C:** Specify upper fan outlet for upward air discharge when placing orders (not for outdoor units). N.B. ! Duct connection size: 2,500 x 800 mm.





### Right-hand version



### Left-hand version

\* If the duct accessory is housed in an insulated casing, the AHU is supplied without the end connection panel. The AHU can also be supplied with full face end connection panel (accessory).

\*\* Width of centre section's casing =  $B + 200$  mm.



Size	A	B	D	E	F	G	H	I	J	K	L	M	N	O	P	Weight, kg
100	1122	3340	1070	187	1200	2400	3440	520	210	470	3314	800	420	2500	1720	4294-4772

### Transport, dimensions and weights

#### Filter and fan sections

See dimensions A and P in the table above.

Weight: fan section = 644-720 kg, filter section = 402-540 kg.

#### Heat exchanger sections

See dimensions D and P in the table above.

Weight: Heat exchanger section = 1101-1126 kg.

### Clear space for inspection

A clear space of 1,000 mm should be provided in front of the unit.

### Rated data per fan


Motor shaft power: 2 x 6.5 kW alt. 2 x 10 kW,  
motor control system: 3 x 400 V, 50 Hz

### Electrical connection

See table Electrical data at the end of this section.

# Sizing, installation, dimensions and weights

## GOLD CX, coil heat exchangers, size 120



Motor shaft power: 3 x 10 kW (capacity variant 2)

- Recommended working range for sizing.
- If pressure regulation is used, the air flow can be regulated to zero. However this presupposes a certain static pressure drop in the ducting (approx. 50 Pa).

### Min. and max. air flows

The flows specified refer to those that can be preset in the hand-held terminal. The practical flow limits are determined by the external pressure drop.

Size	Min. airflow (on airflow regulation)		Max. airflow	
	m³/h	m³/s	m³/h	m³/s
120	9000	2.50	50400	14.0

Exact sizing can be carried out in the AHU Design air handling unit selection program

# Sizing, installation, dimensions and weights

## GOLD CX, coil heat exchangers, size 120

### Delivery and transport within the site

The GOLD CX 120 is supplied as six separate sections: Two fan sections, two filter sections and two coil heat exchanger sections. The six sections must be fitted together at the building site. The pipework package including the control box can be ordered as accessories and are supplied in unassembled condition for floor or wall mounting (see TBXZ pipework package under Accessories).



The three sections are to be jointed together by bolts and the electrical and control cables are simple to connect.

### Duct connection options


**A:** Specify right-hand or left-hand version when ordering.

**B:** The arrangement of the functional sections can vary. Specify this by selecting fan arrangement 1, 2, 4 or 5 when placing orders. For fan arrangement 4 and 5, you should also specify: supply air in upper or lower level.

**C:** Specify upper fan outlet for upward air discharge when placing orders (not for outdoor units). N.B. ! Duct connection size: 2,500 x 800 mm.




### Right-hand version



### Left-hand version

\* If the duct accessory is housed in an insulated casing, the AHU is supplied without the end connection panel. The AHU can also be supplied with full face end connection panel (accessory).

\*\* Width of centre section's casing =  $B + 200$  mm.



Size	A	B	D	E	F	G	H	I	J	K	L	M	N	O	P	Weight, kg
120	1122	3340	1070	187	1200	2400	3440	520	210	470	3314	800	420	2500	1720	4494-4990

### Transport, dimensions and weights

#### Filter and fan sections

See dimensions A and P in the table above.

Weight: fan section = 744-829 kg, filter section = 402-540 kg.

#### Heat exchanger sections

See dimensions D and P in the table above.

Weight: Heat exchanger section = 1101-1126 kg.

### Clear space for inspection

A clear space of 1,000 mm should be provided in front of the unit.

### Rated data per fan

Motor shaft power: 3 x 6.5 kW or 3 x 10 kW,  
motor control system: 3 x 400 V, 50 Hz

### Electrical connection

See table Electrical data at the end of this section.

## Sizing, installation, dimensions and weights

### GOLD PX, counterflow heat exchanger, size 014 - 060+

#### Electrical data

Shows the fuse size for different combinations of fan sizes and capacity variants. Fan A or B can be a supply air fan or an extract air fan or vice versa. It is the combination of fan A and B that determines the fuse size.

Electrical connection is 3-phase, 5-wire, 400 V -10/+15%, 50 Hz.

GOLD PX, size	Fan A, size/capacity variant	Fan B, size/capacity variant	Fuse protection (A)
014/020	014-1 (1,6 kW)	014-1 (1,6 kW)	10
	014-1 (1,6 kW)	014-2 (2,4 kW)	10
	014-1 (1,6 kW)	020-1 (2,4 kW)	10
	014-1 (1,6 kW)	020-2 (3,4 kW)	10
	014-2 (2,4 kW)	014-2 (2,4 kW)	10
	014-2 (2,4 kW)	020-1 (2,4 kW)	10
	014-2 (2,4 kW)	020-2 (3,4 kW)	16
	020-1 (2,4 kW)	020-1 (2,4 kW)	10
	020-1 (2,4 kW)	020-2 (3,4 kW)	10
	020-2 (3,4 kW)	020-2 (3,4 kW)	16
025/030	025-1 (2,4 kW)	025-1 (2,4 kW)	10
	025-1 (2,4 kW)	025-2 (3,4 kW)	16
	025-1 (2,4 kW)	030-1 (4,0 kW)	16
	025-1 (2,4 kW)	030-2 (5,0 kW)	16
	025-2 (3,4 kW)	025-2 (3,4 kW)	16
	025-2 (3,4 kW)	030-1 (4,0 kW)	16
	025-2 (3,4 kW)	030-2 (5,0 kW)	16
	030-1 (4,0 kW)	030-1 (4,0 kW)	16
	030-1 (4,0 kW)	030-2 (5,0 kW)	20
	030-2 (5,0 kW)	030-2 (5,0 kW)	20
035/040/040+	35-1 (4,0 kW)	35-1 (4,0 kW)	16
	35-1 (4,0 kW)	35-2 (5,0 kW)	20
	35-1 (4,0 kW)	40-1 (6,5 kW)	20
	35-1 (4,0 kW)	40-2 (10 kW)	25
	35-2 (5,0 kW)	35-2 (5,0 kW)	20
	35-2 (5,0 kW)	40-1 (6,5 kW)	25
	35-2 (5,0 kW)	40-2 (10 kW)	25
	40-1 (6,5 kW)	40-1 (6,5 kW)	25
	40-1 (6,5 kW)	40-2 (10 kW)	32
	40-2 (10 kW)	40-2 (10 kW)	40
050+/060+	50-1 (6,5 kW)	50-1 (6,5 kW)	25
	50-1 (6,5 kW)	50-2 (10 kW)	32
	50-1 (6,5 kW)	60-1 (2 x 4,0 kW)	32
	50-1 (6,5 kW)	60-2 (2 x 6,5 kW)	40
	50-2 (10 kW)	50-2 (10 kW)	32
	50-2 (10 kW)	60-1 (2 x 4,0 kW)	32
	50-2 (10 kW)	60-2 (2 x 6,5 kW)	40
	60-1 (2 x 4,0 kW)	60-1 (2 x 4,0 kW)	32
	60-1 (2 x 4,0 kW)	60-2 (2 x 6,5 kW)	40
	60-2 (2 x 6,5 kW)	60-2 (2 x 6,5 kW)	50

# Sizing, installation, dimensions and weights

## GOLD CX, counterflow heat exchanger, size 035 - 120

### Electrical data

Shows the fuse size for different combinations of fan sizes and capacity variants. Fan A or B can be a supply air fan or an extract air fan or vice versa. It is the combination of fan A and B that determines the fuse size.

Electrical connection is 3-phase, 5-wire, 400 V -10/+15%, 50 Hz.

GOLD CX, size	Fan A, size/capacity variant	Fan B, size/capacity variant	Fuse protection (A)
035/040	35-1 (4,0 kW)	35-1 (4,0 kW)	20
	35-1 (4,0 kW)	35-2 (5,0 kW)	25
	35-1 (4,0 kW)	40-1 (6,5 kW)	25
	35-1 (4,0 kW)	40-2 (10 kW)	32
	35-2 (5,0 kW)	35-2 (5,0 kW)	25
	35-2 (5,0 kW)	40-1 (6,5 kW)	25
	35-2 (5,0 kW)	40-2 (10 kW)	32
	40-1 (6,5 kW)	40-1 (6,5 kW)	32
	40-1 (6,5 kW)	40-2 (10 kW)	32
	40-2 (10 kW)	40-2 (10 kW)	40
050/060	50-1 (6,5 kW)	50-1 (6,5 kW)	32
	50-1 (6,5 kW)	50-2 (10 kW)	40
	50-1 (6,5 kW)	60-1 (2 x 4,0 kW)	40
	50-1 (6,5 kW)	60-2 (2 x 6,5 kW)	40
	50-2 (10 kW)	50-2 (10 kW)	40
	50-2 (10 kW)	60-1 (2 x 4,0 kW)	40
	50-2 (10 kW)	60-2 (2 x 6,5 kW)	50
	60-1 (2 x 4,0 kW)	60-1 (2 x 4,0 kW)	40
	60-1 (2 x 4,0 kW)	60-2 (2 x 6,5 kW)	50
	60-2 (2 x 6,5 kW)	60-2 (2 x 6,5 kW)	63
070/080	70-1 (2 x 4,0 kW)	70-1 (2 x 4,0 kW)	40
	70-1 (2 x 4,0 kW)	70-2 (2 x 6,5 kW)	50
	70-1 (2 x 4,0 kW)	80-1 (2 x 6,5 kW)	50
	70-1 (2 x 4,0 kW)	80-2 (2 x 10 kW)	63
	70-2 (2 x 6,5 kW)	70-2 (2 x 6,5 kW)	63
	70-2 (2 x 6,5 kW)	80-1 (2 x 6,5 kW)	63
	70-2 (2 x 6,5 kW)	80-2 (2 x 10 kW)	63
	80-1 (2 x 6,5 kW)	80-1 (2 x 6,5 kW)	63
	80-1 (2 x 6,5 kW)	80-2 (2 x 10 kW)	80
	80-2 (2 x 10 kW)	80-2 (2 x 10 kW)	80
100	100-1 (2 x 6,5 kW)	100-1 (2 x 6,5 kW)	50
	100-1 (2 x 6,5 kW)	100-2 (2 x 10 kW)	63
	100-2 (2 x 10 kW)	100-2 (2 x 10 kW)	80
120	120-1 (3 x 6,5 kW)	120-1 (3 x 6,5 kW)	80
	120-1 (3 x 6,5 kW)	120-2 (3 x 10 kW)	100
	120-2 (3 x 10 kW)	120-2 (3 x 10 kW)	125

